



## LARGE BF150C

- Automotive technology
- VTEC® Technology
- BLAST™ (Boosted Low Speed Torque)
- Lean Burn Control®
- Multi-Port Programmed Fuel Injection (PGM-FI)

# HONDA

## MARINE

### ENGINE

|                                 |                                                  |                         |                                      |
|---------------------------------|--------------------------------------------------|-------------------------|--------------------------------------|
| Type                            | 4-Stroke DOHC, VTEC,<br>4 Cylinder / 16 Valves   | Displacement            | 2,354 cc / 144 cubic in.             |
| Bore & Stroke                   | 87 x 99 mm (3.43 x 3.89 in.)                     | Full Throttle RPM Range | 5,000-6,000 RPM                      |
| Propshaft Rated Horsepower (HP) | 150 hp @ 5,500 RPM                               | Cooling System          | Water Cooled                         |
| Fuel Delivery                   | Programmed Electronic Fuel Injection<br>(PGM-FI) | Recommended Fuel        | Unleaded Gas. (Min. Pump Octane 86)  |
| Tank Capacity                   | N/A                                              | Ignition System         | Microcomputer Programmed             |
| Starting System                 | Electric                                         | Exhaust                 | Through Prop Hub                     |
| Lubrication                     | Wet Sump                                         | Recommended Oil         | Honda 10W30 FC-W™ outboard motor oil |
| Oil Capacity                    | 6.70 L (7.08 US qt) with oil filter repl.        | Trim Range              | -4° to +16°                          |
| Tilt Range                      | 72°                                              | Steering Angle          | 30°                                  |

### DRIVE

|            |          |            |       |
|------------|----------|------------|-------|
| Gear Ratio | 2.14 : 1 | Gear Shift | F-N-R |
|------------|----------|------------|-------|

### EQUIPMENT

|                             |                                     |                             |          |
|-----------------------------|-------------------------------------|-----------------------------|----------|
| Alternator (Manual Start)   | N/A                                 | Alternator (Electric Start) | 51 amp   |
| Battery Charging Power      | 30 amp @1000 RPM 40 amp @2,000+ RPM | Power Tilt                  | N/A      |
| Power Trim & Tilt           | Standard                            | Gas Assisted Tilt           | N/A      |
| Oil Pressure Alert          | Standard                            | Over Rev-Limiter            | Standard |
| Temperature Alert           | Standard                            | Water in Fuel Alert         | Standard |
| Battery Condition Alert     | Standard                            | Speedometer Pickup          | Standard |
| Variable Speed Trolling Kit | Optional                            | Rudder Meter Kit            | N/A      |
| Tilt Limiter Kit            | Standard                            | Trolling Mode Range         | N/A      |
| Cruise Control Range        | N/A                                 |                             |          |

### DIMENSIONS

|                         |                 |                         |                 |
|-------------------------|-----------------|-------------------------|-----------------|
| Overall Width           | 610 mm / 24 in. | Transom Height (L-Type) | 508 mm / 20 in. |
| Transom Height (X-Type) | 635 mm / 25 in. |                         |                 |

### PROPELLER

|                                     |          |                                     |     |
|-------------------------------------|----------|-------------------------------------|-----|
| Propeller Type (Material)           | Optional | Propeller Diameter x Pitch (S-Type) | N/A |
| Propeller Diameter x Pitch (L-Type) | N/A      | Propeller Diameter x Pitch (BF(P))  | N/A |

| DRY WEIGHT |                  |           |                                              |
|------------|------------------|-----------|----------------------------------------------|
| SH type    | N/A              | SCHC-Type | N/A                                          |
| SHGC-Type  | N/A              | SHS-Type  | N/A                                          |
| SRC-Type   | N/A              | LH type   | 217 kg / 478 lb.<br>(With propeller mounted) |
| LCHC-Type  | N/A              | LHTC-Type | N/A                                          |
| LHGC-Type  | N/A              | LRTC-Type | N/A                                          |
| L-Type     | N/A              | X-Type    | 221 kg / 487 lb.                             |
| XC-Type    | 224 kg / 494 lb. | XRTC-Type | N/A                                          |
| XX-Type    | N/A              | U-Type    | N/A                                          |
| UC-Type    | N/A              |           |                                              |

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.  
For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.  
®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.